



Aurora Exploration Update – 221m @ 4.72 g/t Au.

Toronto, Ontario: April 2, 2007 – The Company is pleased to report highlights of seventeen diamond drill holes from four different zones at its' 100% owned Aurora Property, Guyana.

Rory's Knoll

The Company currently has two diamond drill rigs committed to exploring and delineating the deeper sections of the Rory's Knoll mineralized zone utilizing the Devico™ directional drilling technology. This program is designed to explore for gold mineralization between vertical depths of 600 metres to 1200 metres below surface and to position acceptable "piercing point" density for resource delineation calculation.

Holes RKD-60DV2 and RKD-60DV3L are the second and third holes designed to explore for gold mineralization between vertical depths of approximately 600 metres and 800 metres below surface. Both holes explored the eastern portion of the deposit, with RKD-60DV3L tracing the eastern edge of the deposit at these depths. Assay results are summarized below.

| Hole # | Location | Mineralized Core Length(m) | | | Grade | |
|-------------|---|---------------------------------|---------------------------------------|---------------|--------------|------|
| | | From | To | Length | g/t Au | |
| RKD-60DV2 | Kick-off point at 501m from RKD-60 including | 687 | 690 | 3.00 | 2.62 | |
| | | 731 | 952.95 | 221.95 | 4.72 | |
| | | 4.52 (cut to 25 g/t Au) | | | | |
| | | 731 | 795 | 64.00 | 8.58 | |
| | | 8.13 (cut to 25 g/t Au) | | | | |
| | | 731 | 741 | 10.00 | 17.98 | |
| | | 16.63 (cut to 25 g/t Au) | | | | |
| | | 757.5 | 783 | 25.50 | 11.57 | |
| | | 10.96 (cut to 25 g/t Au) | | | | |
| | | 807 | 817.5 | 10.50 | 9.10 | |
| | | 8.48 (cut to 25 g/t Au) | | | | |
| | | 925.5 | 936 | 10.50 | 8.06 | |
| | | 7.28 (cut to 25 g/t Au) | | | | |
| | | RKD-60DV3 | Kick-off point at 492m from RKD-60 | 967.5 | 973 | 5.50 |
| 1017 | 1018 | | | 1.00 | 11.48 | |
| 804 | 812 | | | 8.00 | 2.05 | |

| Hole # | Location | Mineralized Core Length(m) | | | Grade |
|-----------|---------------------------------------|----------------------------|-----|--------|--------|
| | | From | To | Length | g/t Au |
| RKD-60DV3 | Kick-off point at 492m from RKD-60 | 822 | 866 | 44.00 | 4.27 |
| | | 3.71 (cut to 25 g/t Au) | | | |
| | Including | 846 | 856 | 10.00 | 13.83 |
| | | 11.36 (cut to 25 g/t Au) | | | |

*Distances are down hole depths and are not absolute vertical distances from surface

Higher grade gold mineralization was intersected in both holes with hole RKD-60DV2 returning 8.58 g/t Au over 64 metres.

Hole RKD-62DV1L is the first “cut” off of mother hole RKD-62. The “62” series of holes are designed to explore for gold mineralization between approximate vertical depths of 1000 metres to 1200 metres. Results are summarized below.

| Hole # | Location | Mineralized Core Length (m) | | | Grade |
|------------|--|-----------------------------|--------|--------|--------|
| | | From | To | Length | g/t Au |
| RKD-62DV1L | Kick-off point at 510m from RKD-62 | 1089 | 1417.5 | 328.50 | 2.43 |
| | | 2.40 (cut to 25 g/t Au) | | | |
| | Including | 1102.5 | 1113 | 10.50 | 4.41 |
| | | 1141.5 | 1152 | 10.50 | 7.70 |
| | | 7.50 (cut to 25 g/t Au) | | | |
| | | 1146 | 1150 | 4.00 | 8.68 |
| | | 8.25 (cut to 25 g/t Au) | | | |
| | | 1165.5 | 1185 | 19.50 | 6.27 |
| | | 6.02 (cut to 25 g/t Au) | | | |
| | | 1171.5 | 1180.5 | 9.00 | 10.85 |
| | | 10.29 (cut to 25 g/t Au) | | | |
| | | 1225.5 | 1234.5 | 9.00 | 3.61 |
| | | 1239 | 1246.5 | 7.50 | 4.92 |
| | | 1255.5 | 1281 | 25.50 | 4.74 |
| | | 4.54 (cut to 25 g/t Au) | | | |
| | | 1263 | 1269 | 6.00 | 11.13 |
| | | 10.26 (cut to 25 g/t Au) | | | |
| | | 1309.5 | 1317 | 7.50 | 4.92 |
| | | 1359 | 1375.5 | 16.50 | 3.25 |
| | | 1392 | 1402.5 | 10.50 | 3.18 |

*Distances are down hole depths and are not absolute vertical distances from surface

Additional high grade gold mineralization was intersected in the eastern portion of the Rory’s Knoll zone - 10.5 metres @ 7.70 g/t Au, 19.5 metres @ 6.27 g/t Au and 6 metres @ 11.13 g/t Au.

Drilling to date has established a very strong probability that high grade gold mineralization, amenable to underground mining, exists below the open pit portion of the Rory’s Knoll zone. In addition the zone remains vertically and laterally open at depth. An aggressive drill program continues in this area.

Aleck Hill – Saprolite & Primary Zone Drilling

The Company reports an additional twelve holes from near surface drilling in the Aleck Hill zone approximately one kilometer west of Rory's Knoll. Better values were obtained in the near surface portion of this zone, with hole SPD-39 returning 18 metres @ 6.8 g/t Au and hole SPD-40 intersecting 19.59 g/t Au over 15 metres.

| Hole # | Location | | Azimuth | Dip | Mineralized Core Length (m) | | | Grade g/t Au |
|---------|----------|------|---------|-----------|---------------------------------|--------|--------|-----------------|
| | North | East | | | From | To | Length | |
| SPD-39 | 9650 | 9760 | 90 | -50 | 25.5 | 43.5 | 18.00 | 6.80 |
| | | | | | 6.54 (cut to 25 g/t Au) | | | |
| | | | | including | 34.5 | 42.5 | 8.00 | 11.50 |
| | | | | | 10.92 (cut to 25 g/t Au) | | | |
| | | | | | 50 | 51 | 1.00 | 27.70 |
| SPD-39A | 9650 | 9760 | 90 | -45 | 27 | 40.5 | 13.50 | 3.36 |
| | | | | including | 36 | 39 | 3.00 | 8.89 |
| | | | | | 45.15 | 47.6 | 2.45 | 25.60 |
| | | | | | 14.91 (cut to 25 g/t Au) | | | |
| SPD-40 | 10150 | 9851 | 90 | -45 | 25 | 28 | 3.00 | 1.18 |
| | | | | | 37 | 40 | 3.00 | 2.50 |
| | | | | | 47.5 | 62.5 | 15.00 | 19.59 |
| | | | | | 8.88 (cut to 25 g/t Au) | | | |
| | | | | including | 52 | 59.5 | 7.50 | 38.46 |
| | | | | | 17.04 (cut to 25 g/t Au) | | | |
| SPD-41 | 10150 | 9850 | 90 | -60 | 27 | 28.5 | 1.50 | 1.03 |
| | | | | | 60 | 73.5 | 13.50 | 4.91 |
| | | | | including | 63 | 67.5 | 4.50 | 10.83 |
| SPD-42 | 10200 | 9841 | 90 | -45 | no significant results | | | |
| SPD-43 | 10200 | 9841 | 90 | -60 | no significant results | | | |
| SPD-44 | 9550 | 9851 | 90 | -45 | no significant results | | | |
| SPD-45 | 9550 | 9850 | 90 | -60 | no significant results | | | |
| SPD-46 | 9500 | 9801 | 90 | -45 | 44.2 | 45.2 | 1.00 | 7.32 |
| SPD-47 | 9500 | 9800 | 90 | -60 | no significant results | | | |
| SPD-48 | 9450 | 9851 | 90 | -45 | no significant results | | | |
| SPD-49 | 9450 | 9851 | 90 | -60 | no significant results | | | |
| AHD-40 | 10050 | 9609 | 90 | -67 | 109 | 116.5 | 7.50 | 2.90 |
| | | | | | 243.6 | 247 | 3.40 | 2.55 |
| | | | | | 277 | 289.25 | 12.25 | 1.65 |
| | | | | | 324.6 | 326.6 | 2.00 | 1.66 |
| AHD-41 | 10100 | 9610 | 90 | -65 | 93.45 | 94.45 | 1.00 | 1.10 |
| | | | | | 137 | 144 | 7.00 | 3.25 |
| | | | | | 181 | 193 | 12.00 | 0.85 |
| | | | | | 272 | 289.35 | 17.35 | 1.01 |
| AHD-42 | 10150 | 9614 | 90 | -60 | 251.4 | 259 | 7.60 | 1.08 |
| | | | | | 264 | 265.2 | 1.20 | 1.30 |

*Distances are down hole depths and are not absolute vertical distances from surface

Drilling is ongoing in the Aleck Hill area.

Ongoing Exploration

The company continues to execute a very aggressive regional exploration program beyond the eight mineralized zones discovered in the golden mile. This regional program includes:

1. Approximately 2,500 auger samples have been collected to the north west of the golden mile. The southern portion of this is on strike with the golden mile and the area contains elevated stream sediment values.
2. An induced polarization survey is planned for the swamp vein area (1.3 km south of Rory's Knoll) to further define gold mineralization reported in the previous release.
3. Trenching in "area 4" southwest of the golden mile has exposed quartz vein stockworks with visible gold.
4. Field work in the unexplored area of historical workings locally known as "Caleb's workings" has uncovered underground gold workings surrounded by large areas that have been mined by hydraulic methods. It is located "on strike" of the regional northwesterly trending structural control of mineralization and is approximately 5km southeast of the Golden Square Mile. An exploration crew is now assigned in this area.
5. Exploratory drilling southeast of Rory's Knoll in the "KRD zone" has intersected 6.8 metres @ 3.47 g/t Au (between 154.9 to 161.7 metres). Follow up drilling is ongoing in this area.

About Guyana Goldfields

The Aurora exploration and drilling program is being carried out under the direction of Mr. Augusto Flores IV, a qualified person within the meaning of National Instrument 43-101. Mr. Flores has reviewed the exploration results contained in this news release. Core is split, with half sent to laboratories for fire assaying. The Company is currently utilizing the services of two independent laboratories, one of which is Loring Laboratories, a Canadian owned and operated facility, as well as the laboratory of a major Canadian mining company. The Company maintains an archive of half core samples and a photographic record of all cores for future reference. Sample blanks, duplicates and recognized standards were inserted into the sample stream at regular intervals.

Guyana Goldfields Inc is a Canadian based mineral exploration Company primarily focused on the exploration and development of gold deposits in the Guiana Shield of South America. The Guiana Shield is in the northern part of the Amazon Craton and covers parts of Guyana, Venezuela, Suriname, French Guyana and northern Brazil.

The Company holds advanced exploration projects in various stages of development and has been operating in Guyana continuously since 1996.

The Company currently has approximately (CDN) \$30 million in cash and no debt.

Additional Information

Information is available on the Company's website at www.guygold.com and on www.sedar.com and through the Company's offices at:

Suite 301-141 Adelaide St. West
Toronto, ON, Canada
M5H 3L5

Phone: 416-628-5936
Fax: 416-628-5935
E-mail: psheridan@guygold.com

Attention: Patrick Sheridan Jr. President & C.E.O.

The TSX has not reviewed and does not accept responsibility for the adequacy or accuracy of this release.